



# Ø 100~Ø 230 高精度スピンドル

※ 最適スピードを選定いたしますのでお問い合わせください。

Model / application	Housing Diameter	Power	Max Speed	Tool Change Tool Interface	Bearing
 SW100-3033C-H32E (engraving)	Ø 100	3.3KW	30,000rpm	(auto) HSK E32	ceramic
 SW100-1205C-B40 Auto-Glass grinding	Ø 100	5KW	12,000rpm	(auto) BT40(ISO40)	ceramic
 SW110-1255C-T LCD glass grinding	Ø 110	5.5KW	12,000rpm	(manual) Special Taper	ceramic
 SW110-1255C-TT LCD glass grinding (rotary joint)	Ø 110	5.5KW	12,000rpm	(manual) Special Taper	ceramic
 SW110-2455CT-H32E (machine tool) (rotary joint)	Ø 110	5.5KW	24,000rpm	(auto) HSK E32(BT30)	ceramic
 SW120-2415C-B30 (machine tool)	Ø 120	15KW	24,000rpm	(auto) BT30(HSK40)	ceramic
 SW120-2415CT-B30EC (machine tool)	Ø 120	15KW	24,000rpm	(auto) BT30(HSK40)	ceramic
 SW140-2425C-H50A (machine tool)	Ø 140	25KW	24,000rpm	(auto) HSK A50(BT40)	ceramic
 SW150-2425CT-H40AEC (machine tool) (rotary joint)	Ø 150	25KW	24,000rpm	(auto) A40	ceramic
 SW170-2425COT-H63AEC (machine tool) (oil mist) (rotary joint)	Ø 170	25KW	24,000rpm	(auto) HSK A63(BT40)	ceramic
 SW230-2440CO-H63AEC (machine tool) (oil mist)	Ø 230	40KW	24,000rpm	(auto) HSK A63	ceramic

Option : oil mist, mini encoder, rotary joint